



P.C.B LAYOUT

Number Of Position	DIMENSIONS		
	A	B	C
06	15.24	12.94	5.08
08	17.78	15.84	7.62
10	20.32	18.02	10.16
12	22.86	20.56	12.70
14	25.40	23.10	15.24
16	27.94	25.64	17.78
20	33.02	30.72	22.86
24	38.10	35.80	27.94
26	40.64	38.34	30.48
30	45.72	43.42	35.56
32	48.26	45.96	38.10
34	50.80	48.50	40.64
40	58.42	56.12	48.26
44	63.50	61.20	53.34
50	71.12	68.82	60.96
60	83.82	81.52	73.66
64	88.90	86.60	78.74

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0
CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 3A
OPERATING TEMPERATURE: -25°C TO +105°C
DIELECTRIC WITHSTANDING : AC 500 V
CONTACT RESISTANCE : 20 MOHM MAX
INSULATION RESISTANCE : 1000 MEGAOHMS MIN

B-D-xx-LF
LEADFREE
06-64WAY

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. B-D-xx		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± ANG	DESCRIP TION:			
DWG NO. B-D-xx		DRAWING BY						
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE	